A4 Mono Printer and MFP



RICOH P 311 M 320F





Stability and Performance

Ensure uninterrupted workflow with print-on-demand from anywhere functionality

Easy to change, long-lasting print cartridges

RICOH P 311 and M 320F offer an All-in-One print cartridge with a long-lasting 7,000 print yield. When you do need to replace the cartridge, there's no disruption to your workflow. Simply slot in the new one via the convenient full front-access design.





*Image shown is with optional tray

Easy document sharing digitally

The feature-rich RICOH M 320F multi-function printer is made for easy sharing of all your important information. The 35-sheet Automatic Reversing Document Feeder (ARDF) allows you to scan and send a full-colour presentation to colleagues for review instantly via multiple Scan-to capabilities, including Scan-to-Email, FTP, Folder, USB drive and more.

Work from anywhere

Access and share all your documents even when not in the office via the RICOH Smart Device Connector app on your mobile device. Mopria® or AirPrint® lets you send print jobs directly to your RICOH printer from your mobile phone. Once you're back in the office, simply pair your Android® device via the Near Field Communications (NFC) tag on the printer to authenticate and transfer information and print.





Security is in our DNA

Recognising your need to keep your data secure, we've added robust security layers. Protect confidential documents from unauthorised viewing with the Locked Print function. Network encryption also ensures data transmission remains secure.

RICOH P 311 / M 320F

MAIN SPECIFICATIONS

MODEL		RICOH P 311	RICOH M 320F
GENERAL			
Configuration		Desktop Laser (Mono)	
Technology		Print	
Function(s) Display panel		4-Line operation LCD	Print, Copy, Scan, Fax 4.3" colour touch panel
Processor		350 MHz	400 MHz
Memory		128 MB	256 MB
Mobile capability		RICOH Smart Device Connector, Apple AirPrint®, Mopria®	
Printer language		PCL5e, PCL6, PostS	cript 3 emulation
Network protocol		TCP/IP	
Interface	Standard	10Base-T/100Base-Tx (Ethernet), USB 2.0 Type A x 1— rear, USB 2.0 Type B— rear, NFC tag IEEE 802.11a/b/q/n/ac (Wire	10Base-T/100Base-Tx (Ethernet) USB 2.0 Type A x 2—1 rear, NFC tag
	Optional Windows®	Windows® 8.1, Windows® 10, Windows® Server 2012, Windows®	· · · · · · · · · · · · · · · · · · ·
Operating system	Mac	Mac OS v10.10 - v11	
	Other	Linux	
PRINTER			
Duplex printing		Auto	
Print speed (A4)		32 ppm (Simplex), 13 ppm (Duplex)	
First print out time		7.1 sec	
Warm up time		26 seconds or less	30 seconds or less
Print resolution		600 x 600 dpi (Default), Windows ®: 600 x 600 dpi, 1,200 x 600 dpi, 1,200 x 1,200 dpi MAC : 600 x 600 dpi Linux : 600 x 600 dpi, 1,200 x 1,200 dpi	
Average print volume		700 - 5,800 pages	
Duty cycle		35,000 pages/month	
COPIER			Heat 22
Copy speed (A4) Document feeder type		-	Up to 32 ppm Automatic Reversing Document Feeder
Document feeder type Document feeder capacity		-	Automatic Reversing Document Feeder 35 sheets
Resolution		_	300 x 600 dpi (ARDF), 600 x 600 dpi (Platen)
Multiple copy		_	Up to 99
			Zoom Range: 25%-400%, Image density: 5 levels, Image quality: Text, Photo, Mixe
Copy features		·	Combined Copy, Memory Copy, ID Card Copy, Series Copy
SCANNER			
Scan speed (A4 ARDF)		<u>-</u>	Mono: 13 impressions/minute, Colour: 4.5 impressions/minute
Resolution Original size		<u>-</u>	600 x 600 dpi (ARDF), 1,200 x 1,200 dpi (Platen), 19,200 x 19,200 dpi (PC TWAIN) A4
Bundled drivers		<u> </u>	Network TWAIN, WIA
Scan to		-	Scan to email, Scan to folder, Scan to FTP, Scan to USB, TWAIN scanning
FACSIMILE			
Circuit		-	PSTN, PABX
Compatibility		-	T.30 (ITU-T SuperG3)
Resolution		-	Horizontal: 200 dpi-8dots/mm, Vertical 100 dpi-3.85dots/mm, 200 dpi-7.7dots/mm
Transmission speed		-	33.6 Kbps—2,400 bps with automatic shift down
Compression method		-	MH, MR, MMR
Reception features		-	Automatic, Paperless fax, Manual, Main scan auto reduction
Other supported features		-	Quick dial—8 (20 digits for name, 40 digits for numbers), Speed dial—100 (20 digits name, 40 digits for numbers), Label registration for Quick/Speed, Redial—automatic manual, Redial included lime—2 selections (5 minutes: default, 6 minutes), Only red last number, Direct fax number entry
SECURITY			
Authentication PAPER HANDLING		Locked	Print
Recommended paper size		A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican Oficio, Indian Legal, Envelopes, Australian Foolscap	
		250 sheets (Bypass: 50 sheets), Maximum: 300 sheets Paper Bank PB1130: 250 sheets, Maximum 550 sheets	
Paper input capacity	Standard With optional paper trav		
Paper input capacity	Standard With optional paper tray		
Paper input capacity Paper output capacity		Paper Bank PB1130: 250 she	ets, Maximum 550 sheets 50 sheets
Paper input capacity Paper output capacity Paper weight		Paper Bank PB1130: 250 she 125 sheets	ets, Maximum 550 sheets 50 sheets
Paper input capacity Paper output capacity Paper weight ECOLOGY	With optional paper tray	Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm	ets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm
Paper input capacity Paper output capacity Paper weight ECOLOGY Dimensions (W x D x H) Weight	With optional paper tray	Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg	ets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg
Paper input capacity Paper output capacity Paper weight ECOLOGY Dimensions (W x D x H) Weight Power consumption (Ma	With optional paper tray	Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacifi	ets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg 2), 920 W (Taiwan)
Paper input capacity Paper output capacity Paper weight ECOLOGY Dimensions (W x D x H) Weight Power consumption (Ma	With optional paper tray	Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific), 64.9 W (Taiwan)	2 g/m ² 405 mm x 392 mm x 420 mm Less than 18.0 kg 2), 920 W (Taiwan) 65.7 W (Asia Pacific), 65.7 W (Taiwan)
Paper input capacity Paper output capacity Paper weight ECOLOGY Dimensions (W x D x H) Weight Power consumption (Markedy mode Energy saver (Sleep)	With optional paper tray	Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific), 64.9 W (Taiwan) 0.72 W (Asia Pacific), 0.66 W (Taiwan)	2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg 2), 920 W (Taiwan) 65.7 W (Asia Pacific), 65.7 W (Taiwan) 0.87 W (Asia Pacific), 0.8 W (Taiwan)
Paper input capacity Paper output capacity Paper weight ECOLOGY Dimensions (W x D x H) Weight Power consumption (Ma Ready mode Energy saver (Sleep) Power source	With optional paper tray	Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific), 64.9 W (Taiwan)	2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg 2), 920 W (Taiwan) 65.7 W (Asia Pacific), 65.7 W (Taiwan) 0.87 W (Asia Pacific), 0.8 W (Taiwan)
Paper input capacity Paper output capacity Paper weight ECOLOGY Dimensions (W x D x H) Weight Power consumption (Ma Ready mode Energy saver (Sleep) Power source CONSUMABLES	With optional paper tray ax)	Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific), 64.9 W (Taiwan) 0.72 W (Asia Pacific), 0.66 W (Taiwan) 220–240 V, 50/60 Hz, 4.3 Amps (Asia Pa	ets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg 2), 920 W (Taiwan) 65.7 W (Asia Pacific), 65.7 W (Taiwan) 0.87 W (Asia Pacific), 0.8 W (Taiwan) iffic), 110 V, 60 Hz, 8.5 Amps (Taiwan)
Paper input capacity Paper output capacity Paper weight ECOLOGY Dimensions (W x D x H) Weight Power consumption (Ma Ready mode Energy saver (Sleep) Power source CONSUMABLES AIO toner cartridges (K) Consumable yield meas	With optional paper tray ax) (Extra high yield) uring method ISO/IEC 1975	Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific), 64.9 W (Taiwan) 0.72 W (Asia Pacific), 0.66 W (Taiwan) 220–240 V, 50/60 Hz, 4.3 Amps (Asia Pa	ets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg 2), 920 W (Taiwan) 65.7 W (Asia Pacific), 65.7 W (Taiwan) 0.87 W (Asia Pacific), 0.8 W (Taiwan) iffic), 110 V, 60 Hz, 8.5 Amps (Taiwan)
Paper input capacity Paper output capacity Paper weight ECOLOGY Dimensions (W x D x H) Weight Power consumption (Ma Ready mode Energy saver (Sleep) Power source CONSUMABLES AIO toner cartridges (K) Consumable yield meas	With optional paper tray ax) (Extra high yield) uring method ISO/IEC 1975	Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific), 64.9 W (Taiwan) 0.72 W (Asia Pacific), 0.66 W (Taiwan) 220–240 V, 50/60 Hz, 4.3 Amps (Asia Pacific) Black: Approx.	ets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg 2), 920 W (Taiwan) 65.7 W (Asia Pacific), 65.7 W (Taiwan) 0.87 W (Asia Pacific), 0.8 W (Taiwan) iffic), 110 V, 60 Hz, 8.5 Amps (Taiwan) 7,000 pages













